

Soundweb OMNI



256p Open Architecture
Digital Signal Processor



The BSS Soundweb OMNI 256p Open Architecture Digital Signal Processor is the most powerful enterprise-grade processor ever developed by BSS. With processing capability that surpasses previous BSS products, the all-new design ensures the seamless handling of today's most complex installations to be future-ready to meet the evolving needs of tomorrow. The 256p features 256x256 Dante/AES67 networked audio channels @ either 48kHz or 96kHz; enterprise-grade network security support; an onboard scripting engine developed by AMX; 8 GPIO ports (fully flexible); 80 AEC channels; 32 VoIP lines; high precision word clock and BNC clock (in/out); dual redundant power supplies, Dante and HControl; 128 channel internal media player with 500GB SSD; full-color, interactive front panel LCD; and more.

FEATURE HIGHLIGHTS

- 256x256 at up to 96kHz Dante/AES67 networked audio channels
- Enterprise-grade network security support
- Onboard scripting engine developed by AMX
- 24/48kHz and 24/96kHz supported bit depth/sample rates
- 8 GPIO ports (fully flexible)
- 80 AEC channels
- 32 VoIP lines
- High precision word clock
- BNC clock (in/out)
- Dual redundant power supplies, Dante and HControl
- 128 channel internal media player with 500GB SSD
- Full-color, interactive front panel LCD
- Choice of centralized or distributed DSP topologies
- Unlimited number of Soundweb OMNI processors can be added to a single project file
- Configurable, controllable and monitorable with AVX software suite
- HARMAN HControl protocol supported
- Public and Private Routing for Dante

HARMAN PROFESSIONAL INC. • 8500 BALBOA BOULEVARD • NORTHRIDGE • CA 91329 • USA • +1 818 893 8411

©2025 HARMAN Professional. All rights reserved. BSS Audio® is a registered trademark of HARMAN Professional Inc. registered in the United States and/or other countries.

* Features, specifications, and appearance are subject to change without notice.

Soundweb OMNI 256p

Open Architecture Digital Signal Processor



GENERAL SPECIFICATIONS

POWER	
Voltage Input	100 - 240 VAC
Power Input	250W
Current Input	2.1A @ 120 VAC - 1.1A @ 240 VAC
Heat Output	853 BTU/Hr
Redundancy	2 Mains cords, 2 mains power supplies, full capability with only 1 supply
THERMAL	
Operating Temp Range	0° - 45° C
Storage Temp	-20° - 60° C
CONTROL GPIO	
8 channel FLEX	Each GPIO pin can be configured as input or output, analog or logic.
Convenience Power	5V +/- 5%, 300 mA overload protected.
Logic Output	Programmable for high/low (0/5v) binary. 20mA source or sink.
Logic Input	Programmable for voltage threshold, 12V max, 10k input resistance to ground.
Analog Output	0 - 12 V DC +/- 2% 10 mA source or sink.
Analog Input	0 - 12 V DC +/- 2% 10k input resistance to ground.
Relay Mode	Open Drain drive capable of 60 mA sink. 12V max off voltage.
ACOUSTIC	
Fan Noise	30 dB SPL A-Weighted MAX 23 dB SPL A-Weighted at Nominal
WORD CLOCK	
Frequencies	48kHz or 96kHz
Accuracy	1 min/yr = 2 ppm
Input	TTL, 75 Ω BNC Connector
Output	TTL, 75 Ω BNC Connector
CONTROL NETWORK	
Connectivity	RJ-45 Gigabit Ethernet (redundant)
Compatibility	HControl
Max Cable Length	100m or 328ft
AUDIO NETWORK	
Connectivity	RJ-45 Gigabit Ethernet (redundant)
Compatibility	Dante and AES67
Capacity	256 channels at 48kHz or 96kHz
Latency	< Set in Dante controller

Soundweb OMNI 256p

Open Architecture Digital Signal Processor



GENERAL SPECIFICATIONS (Cont.)

MEDIA STORAGE	
Capability	Internal SSD
Channel Count	128 channels total
Capacity	>1,500 hours @24bit/96kHz WAV
FRONT PANEL	
Main Operation	LCD Screen 13.4 x 2.5 cm = 4.3" display with 480(RGB) x 800 resolution LCD Screen 1200 x 225 pixel
Status LEDs	DanteLink/Activity HControl Link/Activity, PSU Health
Locate Indicator	Front and Rear
MOUNTING	
Size	19in. (483mm) width x 3.6in. (88mm) height x 17.5in. (445mm) depth (2 RU)
Weight	24.9 lbs (11.3 kgs) gross weight, 19.4 lbs (8.8 kgs) net weight
Rack Type	19in. per EIA-310 standard